

## DECLARATION OF PERFORMANCE

DoP 01-128-14

1	Unique identification code of product-type:	Liquid tape 2K waterproofing
2	Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):	Liquid tape 2K waterproofing, Batch number: See product packaging
3	Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:	Waterproof cement based product, modified with polymer coating in fluid state, capable of bridging the crack, resistant in contact with chlorinated water Class P CM According to EN 14891
4	Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):	Den Braven production s.r.o. Úvalno 353, 793 91 Úvalno, Czech Republic IČO: 26872072 tel.: + 420 554 648 200; fax.: +420 554 648 205, <a href="http://www.denbraven.cz">www.denbraven.cz</a>
5	Name and contact address of the authorized representative whose mandate covers the task specified in Article 12 (2):	not relevant
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:	System 3
7	In case of declaration of performance concerning a construction product covered by a harmonized standard:	The notified body number 1020 – Technický a zkušební ústav Praha s.p. Branch office: Nemanická 441, 370 10 České Budějovice, Czech Republic performed the initial type testing according to EN 14891:2012 (A020-031652) and reaction to fire under system 3
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment:	not relevant
	has been issued	not relevant
	based on	not relevant
9	Declared performance (regarding ZA.1.2):	
	Essential characteristics	Performance
	Initial tensile strength	≥ 0,5 N/mm <sup>2</sup>
	Tensile properties after immersion in water	≥ 0,5 N/mm <sup>2</sup>
	Tensile properties after thermal aging	≥ 0,5 N/mm <sup>2</sup>
	Tensile properties after immersion in lime water	≥ 0,5 N/mm <sup>2</sup>
	Water tightness	NF
	Crack bridging ability in standard conditions	≥ 0,75 mm
	Tensile properties after cyclic freeze-thaw	≥ 0,5 N/mm <sup>2</sup>
	Tensile properties after contact with chlorinated water	≥ 0,5 N/mm <sup>2</sup>
	Release of chemicals dangerous to the environment and health	NPD (*)
	Harmonized technical specification	
	EN 14891:2012	
10	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.	

(\*) See material safety data sheet, NPD: No Performance Determined, NF: No Failure

Signed for and on behalf of the manufacturer by:

Ing. Kamil Šmidák  
Marketing manager

In Úvalno, August 7th, 2014



 **Den Braven**  
Czech and Slovak a.s.  
793 91 Úvalno 353, tel.: 554 648 200, fax: 554 648 205  
IČO: 26 87 20 72, DIČ: CZ 26 87 20 72

Údaje o zápisu do OR: Zapsáno KS Ostrava, oddíl B, vložka 2951

Den Braven Czech and Slovak a.s.

Adresa: 793 91 Úvalno 353, tel.: 554 648 200, fax: 554 648 205, Česká republika

Bankovní spojení: KB Krnov, č. ú. 19 - 0848810297 / 0100

[info@denbraven.cz](mailto:info@denbraven.cz)

IČO: 26872072, DIČ: CZ26872072

[www.denbraven.cz](http://www.denbraven.cz)